

EV Charging Point 40kW DC Charging Station (3-phase)

EVIQ-40S-P RFID

EVIQ-40D-P RFID Page 1

EVIQ-40D-P-CM Page 2

EVIQ-40D-P-CC Page 3



Features

- **Compact design**
- **Free app**
- **Full protection**
Full electrical protection, over/under temperature protection, etc
- **Stable**
IP54 protection grade, usable in harsh environments
- **Intelligent**
Intelligent power adjustment, emergency stop, WiFi/Ethernet/4G
- **Flexible**
25 - 40kW power control
- **Time Shifting**
Utilise off-peak energy tariffs
- **Easy to install**



Specification

Input & Output

Voltage	AC230~415V
Input Frequency	45~65HZ
Output Voltage	250~750V DC
Max Output Current	0~33.3A/0~60A/per phase
Connection	DC Gun *1

Protection

Overload Protection	Yes
Short Circuit Protection	Yes
Earth Leakage Protection	Yes
Over-temp Protection	Yes

Function & Accessory

Ethernet/WIFI/4G	Yes/Opt/Opt
Supported Payment	RFID/QR(Standard)
LED Indicator Light	Yes
Emergency Stop Button	Yes
Cable	4m
Load Balancing distance	> 15m meter (3PHM)

Working Environment

Protection Degree	IP54
Operating Temperature	-20°C ~+65°C
Standby Power Consumption	<25W
Cooling	Forced air cooling
Noise Emission	≥65db

Mechanical

Dimensions (w/h/d)	540 x 760 x 271mm
Weight	55Kg
Wall-mounting Bracket/	Yes/
Ground-mounting Pole	Opt

Contact us for more information

sara.mason-parker@gl-e.uk • ryan.shemwell@gl-e.uk • 01905 610200



EV Charging Point 40kW DC Charging Station (3-phase)

EVIQ-40D-P-CM

EVIQ-40D-P-RFID Page 1

EVIQ-40D-P-CM Page 2

EVIQ-40D-P-CC Page 3



Features

- **Compact design**
- **Free app**
- **Full protection**
Full electrical protection, over/under temperature protection, etc
- **Stable**
IP54 protection grade, usable in harsh environments
- **Intelligent**
Intelligent power adjustment, emergency stop, WiFi/Ethernet/4G
- **Flexible**
25 - 40kW power control
- **Time Shifting**
Utilise off-peak energy tariffs
- **Easy to install**

Specification

Input & Output

Voltage	260~530V AC
Input Frequency	50Hz/60Hz
DC plug type	CCS, CHadeMO double plugs
Output Voltage	CCS(150-750V), CHadeMO(150-500V)
Max Output Current	40kW

Protection

Overload Protection	Yes
Short Circuit Protection	Yes
Earth Leakage Protection	Yes
Over-temp Protection	Yes

Function & Accessory

Display	7in touch screen
Ethernet/WIFI/4G	Yes/Opt/Opt
Supported Payment	RFID/QR(Standard)
LED Indicator Light	Yes
Emergency Stop Button	Yes
Cable	5m

Working Environment

Protection Degree	IP54
Operating Temperature	-20°C ~+65°C
Standby Power Consumption	<25W
Cooling	Forced air cooling
Noise Emission	≥65db

Mechanical

Dimensions (w/h/d)	80 x 560 x 270mm
Weight	90Kg

Contact us for more information

sara.mason-parker@gl-e.uk • ryan.shemwell@gl-e.uk • 01905 610200





EV Charging Point 40kW DC Charging Station (3-phase)

EVIQ-40D-P-CC

EVIQ-40D-P-RFID Page 1

EVIQ-40D-P-CM Page 2

EVIQ-40D-P-CC Page 3



Features

- **Compact design**
- **Free app**
- **Full protection**
Full electrical protection, over/under temperature protection, etc
- **Stable**
IP54 protection grade, usable in harsh environments
- **Intelligent**
Intelligent power adjustment, emergency stop, WiFi/Ethernet/4G
- **Flexible**
25 - 40kW power control
- **Time Shifting**
Utilise off-peak energy tariffs
- **Easy to install**

Specification

Input & Output

Voltage	260~530V AC
Input Frequency	50Hz/60Hz
DC plug type	2 X CCS, double plugs
Output Voltage	CCS(150-750V), CHadeMO(150-500V)
Max Output Current	40kW

Protection

Overload Protection	Yes
Short Circuit Protection	Yes
Earth Leakage Protection	Yes
Over-temp Protection	Yes

Function & Accessory

Display	7in touch screen
Ethernet/WIFI/4G	Yes/Opt/Opt
Supported Payment	RFID/QR(Standard)
LED Indicator Light	Yes
Emergency Stop Button	Yes
Cable	5m

Working Environment

Protection Degree	IP54
Operating Temperature	-20°C ~+50°C
Standby Power Consumption	<25W
Cooling	Forced air cooling
Noise Emission	≥65db

Mechanical

Dimensions (w/h/d)	80 x 560 x 270mm
Weight	90Kg

Contact us for more information

sara.mason-parker@gl-e.uk • ryan.shemwell@gl-e.uk • 01905 610200

